

National PDES Testbed
Report Series

**NIST Express
Working Form
Programmer's
Reference**

Revised November, 1990



NISTIR 4407

National PDES Testbed
Report Series



NIST Express
Working Form
Programmer's
Reference

Stephen Nowland Clark

U.S. DEPARTMENT OF
COMMERCE

Robert A. Mosbacher,
Secretary of Commerce

National Institute of
Standards and Technology
John W. Lyons, Director

November 29, 1990



Disclaimer

No approval or endorsement of any commercial product by the National Institute of Standards and Technology is intended or implied

Unix is a trademark of AT&T Technologies, Inc.

Smalltalk-80 is a trademark of ParcPlace Systems, Inc.

Table Of Contents

| | |
|---|-----------|
| 1 Introduction..... | 1 |
| 1.1 Context..... | 1 |
| 2 Fed-X Control Flow | 1 |
| 2.1 First Pass: Parsing | 2 |
| 2.2 Second Pass: Reference Resolution | 2 |
| 2.3 Third Pass: Output Generation | 3 |
| 3 Working Form Implementation | 3 |
| 3.1 Primitive Types..... | 4 |
| 3.2 Symbol and Construct..... | 4 |
| 3.3 Express Working Form Manager Module | 4 |
| 3.4 Code Organization and Conventions | 4 |
| 3.5 Memory Management and Garbage Collection..... | 5 |
| 4 Writing An Output Module | 5 |
| 4.1 Layout of the C Source | 6 |
| 4.2 Traversing a Schema..... | 7 |
| 4.3 Output Module Linkage Mechanisms..... | 8 |
| 5 Working Form Routines..... | 9 |
| 5.1 Working Form Manager | 9 |
| 5.2 Algorithm..... | 10 |
| 5.3 Case Item | 12 |
| 5.4 Constant | 13 |
| 5.5 Construct..... | 14 |
| 5.6 Entity..... | 14 |
| 5.7 Expression..... | 18 |
| 5.8 Loop Control..... | 24 |
| 5.9 Schema..... | 26 |
| 5.10 Scope..... | 26 |
| 5.11 Statement | 29 |
| 5.12 Symbol..... | 33 |
| 5.13 Type | 34 |
| 5.14 Variable..... | 40 |
| 6 Express Working Form Error Codes..... | 42 |
| Appendix A: References | 47 |

NIST Express Working Form Programmer's Reference

Stephen Nowland Clark

1 Introduction

The NIST Express Working Form [Clark90b], with its associated Express parser, Fed-X, is a Public Domain set of software tools for manipulating information models written in the Express language [Schenck90]. The Express Working Form (WF) is part of the NIST PDES Toolkit [Clark90a]. This reference manual discusses the internals of the Working Form, including the Fed-X parser. The information presented will be of use to programmers who wish to write applications based on the Working Form, including output modules for Fed-X, as well as those who will maintain or modify the Working form or Fed-X. The reader is assumed to be familiar with the design of the Working Form, as presented in [Clark90b].

1.1 Context

The PDES (Product Data Exchange using STEP) activity is the United States' effort in support of the Standard for the Exchange of Product Model Data (STEP), an emerging international standard for the interchange of product data between various vendors' CAD/CAM systems and other manufacturing-related software [Smith88]. A National PDES Testbed has been established at the National Institute of Standards and Technology to provide testing and validation facilities for the emerging standard. The Testbed is funded by the CALS (Computer-aided Acquisition and Logistic Support) program of the Office of the Secretary of Defense. As part of the testing effort, NIST is charged with providing a software toolkit for manipulating PDES data. This NIST PDES Toolkit is an evolving, research-oriented set of software tools. This document is one of a set of reports which describe various aspects of the Toolkit. An overview of the Toolkit is provided in [Clark90a], along with references to the other documents in the set.

For further information on the Express Working Form or other components of the Toolkit, or to obtain a copy of the software, use the attached order form.

2 Fed-X Control Flow

A Fed-X translator consists of three separate passes: parsing, reference resolution, and output generation. The first two passes can be thought of as a single unit which produces an instantiated Working Form. This Working Form can be traversed by an output

module in the third. It is anticipated that users will need output formats other than those provided with the NIST Toolkit. The process of writing a report generator for a new output format is discussed in detail in section 4.

2.1 First Pass: Parsing

The first pass of Fed-X is a fairly straightforward parser, written using the UnixTM parser generation languages, Yacc and Lex. As each construct is parsed, it is added to the Working Form. No attempt is made to resolve symbol references: they are represented by instances of the type `Symbol` (see below), which are replaced in the second pass with the referenced objects.

The grammar used by Fed-X is processed by Bison, a Yacc clone available from the Free Software Foundation.¹ The lexical analyzer is processed by Flex,² a fast, Public Domain implementation of Lex. The analyzer makes use of one feature of Flex which is not present in Lex: it uses an exclusive start condition to scan comments properly. The scanner can easily be rewritten to use only standard start conditions if it is necessary to use Lex. Other differences between Lex and Flex are handled properly by conditional compilation (`#ifdef` .. `#endif` pairs).

2.2 Second Pass: Reference Resolution

The reference resolution pass of Fed-X walks through the Working Form built by the parser and attempts to replace each `Symbol` with the object to which it refers. The name of each symbol is looked up in the scope which is in effect at the point of reference. If a definition for the name is found which makes sense in the current context, the definition replaces the symbol reference. Otherwise, Fed-X prints an error message and proceeds.

In some cases, the changes which must be made when a symbol is resolved are slightly more drastic. For example, the syntax of Express does not distinguish between an identifier and an invocation of a function of no arguments. When a token could be interpreted as either, the parser always guesses that it is a simple identifier. When the second pass determines that one of these objects actually refers to a function, the `Identifier` expression is replaced by an appropriate `Function_Call` expression.

1. The Free Software Foundation (FSF) of Cambridge, Massachusetts is responsible for the GNU Project, whose ultimate goal is to provide a free implementation of the Unix operating system and environment. These tools are not in the Public Domain: FSF retains ownership and copyright privileges, but grants free distribution rights under certain terms. At this writing, further information is available via electronic mail on the Internet from gnu@prep.ai.mit.edu.

2. Vern Paxson's Flex is usually distributed with GNU software, although, being in the Public Domain, it does not come under the FSF licensing restrictions.

Thus, the result of the second pass (in the absence of any errors) is a tightly linked set of structures in which, for example, `Function_Call` expressions reference the called `Algorithms` directly. At this point, it is possible to traverse the data structures without resorting to any further symbol table lookups. The scopes in the Working Form are only needed to resolve external references - e.g., from a STEP physical file.

2.3 Third Pass: Output Generation

The report or output generation pass manages the production of the various output files. In the dynamically linked version of Fed-X, this pass loads successive output modules, calling each one to traverse the Working Form. The dynamic linking mechanism is discussed briefly in [Clark90c]. It is also possible to build a statically linked translator, with a particular output module loaded in at build time; this is, at present, the only mechanism available in an environment which is not derived from BSD 4.2 Unix.

A report generator is an object module, most likely written in C, which has been compiled as a component module for a larger program (i.e., with the `-c` option to a Unix C compiler). In a dynamically linked translator, this object module is linked into the running parser, and its entry point (by convention a function called `print_file()`) is called. The code of this module consists of calls to Express Working Form access functions and to standard output routines. A detailed description of the creation of a new output module appears in section 4.

3 Working Form Implementation

The Express Working Form data abstractions are implemented in ANSI Standard C [ANSI89]. Each abstraction is implemented as one or more classes, using the `Class/Object` modules in `libmisc` [Clark90c]. The data specific to a particular class is encapsulated in a private C `struct`. This structure is never manipulated directly outside of the abstraction's module. For example:

```
/* the actual contents of a Foo */
struct Foo {
    int i;
    double d;
};

typedef Object Foo;

/* Class_Foo is created in FOOinitialize() */
Class Class_Foo;
```

Outside of `Foo`'s module, we will never see a `struct Foo`. We will only see a `Foo`, which is actually an `Object` which ultimately points at a `struct Foo`.

3.1 Primitive Types

The Express Working Form makes use of several modules from the Toolkit general libraries, including the `Class`, `Object`, `Error`, `Linked_List`, and `Dictionary` modules. These are described in [Clark90c]. The underlying representation for all of the Working Form abstractions makes use of the `Class` and `Object` modules.

3.2 Symbol and Construct

The types `Symbol` and `Construct` are, in Object-Oriented terminology, abstract supertypes for the various types in the Working Form. The two are quite similar, both in concept and in implementation. Both have an attribute containing the line number on which the represented construct appears in the source file (probably useful only within Fed-X). A `Symbol` also includes a name and a flag indicating whether the symbol has been resolved.

Abstractions which represent namable objects are subclassed from `Symbol`. These include `Constant`, `Type`, `Variable`, `Algorithm`, `Entity`, and `Schema`. The latter three are actually subclasses of another `Symbol` subclass, `Scope`. Other abstractions (`Case_Item`, `Expression`, `Loop_Control`, and `Statement`) are subclassed from `Construct`.

3.3 Express Working Form Manager Module

In addition to the abstractions discussed in [Clark90b], `libexpress.a` contains one more module, the package manager. Defined in `express.c` and `express.h`, this module includes calls to initialize the entire Express Working Form package, and to run each of the passes of a Fed-X translator.

3.4 Code Organization and Conventions

Each abstraction is implemented as a separate module. Modules share only their interface specifications with other modules. There is one exception to this rule: In order to avoid logistical problems compiling circular type definitions across modules, an Express Working Form module includes any other Working Form modules it uses *after* defining its own private `struct`. Thus, the types defined by these other modules are not yet known at the time an abstraction's private `struct` is defined, and references to these other Working Form types must assume knowledge of their implementations. This is, in fact, not a serious limitation: All of the Working Form types are implemented as `Objects`, which *is* defined when the `struct` is compiled.

A module `Foo` is composed of two C source files, `foo.c` and `foo.h`. The former contains the body of the module, including all non-inlined functions. The latter contains function prototypes for the module, as well as all type and macro definitions. In addition, global variables are defined here, using a mechanism which allows the same declarations to be used both for `extern` declarations in other modules and the actual storage definition in the declaring module. These globals can also be given constant initializers. Finally, `foo.h` contains inline function definitions. In a compiler which supports inline functions, these are declared `static inline` in every module which

`#includes foo.h`, including `foo.c` itself. In other compilers, they are undefined except when included in `foo.c`, when they are compiled as ordinary functions. `foo.c` resides in `~pdes/src/express/`; `foo.h` in `~pdes/include/`.

The type defined by module `Foo` is named `Foo`, and its private structure is `struct Foo`. Access functions are named as `FOOfunction()`; this function prefix is abbreviated for longer abstraction names, so that access functions for type `Foolhardy_Bartender` might be of the form `FOO_BARfunction()`. Some functions may be implemented as macros; these macros are not distinguished typographically from other functions, and are guaranteed not to have unpleasant side effects like evaluating arguments more than once. These macros are thus virtually indistinguishable from functions. Functions which are intended for internal use only are named `FOO_function()`, and are usually `static` as well, unless this is not possible. Global variables are often named `FOO_variable`; most enumeration identifiers and constants are named `FOO_CONSTANT` (although these latter two rules are by no means universal). For example, every abstraction defines a constant `FOO_NULL`, which represents an empty or missing value of the type.

If an instance of `Foo` might contain unresolved Symbols, then there is a function `FOOresolve(...)`, called during Fed-X's second pass, which attempts to resolve all such references and reports any errors found. This call may or may not require a `Scope` as a parameter, depending on the abstraction. For example, an `Algorithm` defines its own local `Scope`, from which the next outer `Scope` (in which the `Algorithm` is defined) can be determined; `ALGresolve()` thus requires no `Scope` parameter. A `Type`, on the other hand, has no way of getting at its `Scope`, so `TYPEresolve()` requires a second parameter indicating the `Scope` in which the `Type` is to be resolved.

3.5 Memory Management and Garbage Collection

In reading various portions of the Express Working Form documentation, one may get the impression that the Working Form does some reasonably intelligent memory management. This is not entirely true. The NIST PDES Toolkit is primarily a research tool. This is especially true of the Express and STEP Working Forms. The Working forms allocate huge chunks of memory without batting an eye, and this memory often is not released until an application exits. Hooks for doing memory management do exist (e.g., `OBJfree()` and reference counts), and some attempt is made to observe them, but this is not given high priority in the current implementation.

4 Writing An Output Module

It is expected that a common use of the Express WF will be to build Express translators. The Fed-X control flow was designed with this application in mind. A programmer who wishes to build such a translator need only write an output module for the target language. We now turn to the topic of writing this output module. The end result of

the process described will be an object module (under Unix, a `.o` file) which can be loaded into Fed-X. This module contains a single entry point which traverses a given Schema and writes its output to a particular file.

The stylistic convention taken in the existing output modules, and which meshes most cleanly with the design of the Working Form data structures, is to define a procedure `FOOprint(Foo foo, FILE* file)` corresponding to each Working Form abstraction. Thus, `SCHEMAprint(Schema schema, FILE* file)` is the conceptual entry point to the output module; an Algorithm is written by the call `ALGprint(Algorithm algorithm, FILE* file)`, etc. With this breakdown, most of the actual output is generated by the routines for Type, Entity, and other concrete Express constructs. The routines for Schema and Scope, on the other hand, control the traversal of the data structures, and produce little or no actual output. For this reason, it is probably useful to base new report generators on existing ones, copying the traversal logic wholesale and modifying only the routines for the concrete objects. The Fed-X-QDES output module (which can be found in `~pdes/src/fedex_qdes/output_smalltalk.c`) has been annotated for this purpose, although the traversal logic has become somewhat convoluted, due to peculiarities of Smalltalk-80™.

4.1 Layout of the C Source

The layout of the C source file for a report generator which will be dynamically loaded is of critical importance, due to the primitive level at which the load is carried out. The very first piece of C source in the file must be the `entry_point()` function, or the loader may find the wrong entry point to the file, resulting in mayhem. Only comments may precede this function; even an `#include` directive may throw off the loader. An output module is normally layed out as shown:

```
void
entry_point(void* schema, void* file)
{
    extern void print_file();
    print_file(schema, file);
}

#include "express.h"

... actual output routines ...

void
print_file(void* schema, void* file)
{
    print_file_header((Schema) schema,
                      (FILE*) file);
    SCHEMAprint((Schema) schema, (FILE*) file);
}
```

```

        print_file_trailer((Schema) schema,
                           (FILE*) file);
    }

```

The `print_file()` function will probably always be quite similar to the one shown, although in many cases, the file header and/or trailer may well be empty, eliminating the need for these calls. In this case, `SCHEMAprint()` and `print_file()` will probably become interchangeable.

Having said all of the above about templates, code layout, and so forth, we add the following note: In the final analysis, the output module really is a free-form piece of C code. There is one and only one rule which must be followed, and this only if the `reprt` generator will be dynamically loaded: The entry point (according to the `a.out` format) to the `.o` file which is produced when the report generator is compiled must be appropriate to be called with a `Schema` and a `FILE*`. The simplest (and safest) way of doing this is to adhere strictly to the layout given, and write an `entry_point()` routine which jumps to the real (conceptual) entry point. But any other mechanism which guarantees this property may be used. Similarly, the layout of the rest of the code is purely conventional. There is no *a priori* reason to write one output routine per data structure, or to use the `print_file()` routine suggested. This approach has simply proved to work nicely for current and past report generators, and seems to provide the shortest path to a new output module. In other words, if you don't like the previous authors' coding style(s), feel free to muck around!

4.2 Traversing a Schema

Following the one-routine-per-abstraction rule, there are two general classes of output routines. Those corresponding to primitive Express constructs (`ENTITYprint()`, `TYPEprint()`, `VARprint()`) will produce most of the actual output, while `SCOPEprint()` (and, to a lesser extent `SCHEMAprint()`) will be responsible for traversing the instantiated working form. A typical definition for `SCOPEprint()` would be:

```

void
SCOPEprint(Scope scope, FILE* file)
{
    Linked_List list;

    list = SCOPEget_types(scope);
    LISTdo(list, type, Type)
        TYPEprint(type, file);
    LISTod;
    LISTfree(list);

    list = SCOPEget_entities(scope);
    LISTdo(list, ent, Entity)
        ENTITYprint(ent, file);
}

```

```

LISTod;
LISTfree(list);

list = SCOPEget_algorithms(scope);
LISTdo(list, alg, Algorithm)
    ALGprint(alg, file);
LISTod;
LISTfree(list);

list = SCOPEget_variables(scope);
LISTdo(list, var, Variable)
    VARprint(var, file);
LISTod;
LISTfree(list);

list = SCOPEget_schemata(scope);
LISTdo(list, schema, Schema)
    SCHEMAprint(schema, file);
LISTod;
LISTfree(list);
}

```

This function traverses the model from the outermost schema inward. All types, entities, algorithms, and variables in a schema are printed (in that order), followed by all definitions for any sub-schemas. The only traversal logic required in `SCHEMAprint()` is simply to call `SCOPEprint()`.

An approach which is taken in the Fed-X-QDES output module is to divide the logical functionality of `SCOPEprint()` into two separate passes, implemented by functions `SCOPEprint_pass1()` and `SCOPEprint_pass2()`. The first pass prints all of the entity definitions, in superclass order (i.e., subclasses are not printed until after their superclasses), without attributes. This is necessary because of some difficulties with forward references in Smalltalk-80. The second pass then looks much like the sample definition of `SCOPEprint()` given above. This multi-pass strategy could also be used to print, for example, all of the type and entity definitions in the entire model, followed by all variable and algorithm definitions.

4.3 Output Module Linkage Mechanisms

One of the powers of Fed-X is the flexibility which it gives a user with regard to generating output. An important component of this flexibility on BSD Unix systems is the dynamic loading of output modules. Both static and dynamic binding of output modules are supported by Fed-X. This is implemented by providing two distinct versions of the Working Form manager. Code common to both versions (including initialization code and the first two passes of Fed-X) is found in `express.c`, which is included by each of the distinct manager modules. The static linking version of the third pass, with-

out any output module, is in `express_static.c`, and the corresponding `express_static.o` is included in `libexpress.a`, making it the default; the dynamic loading version is in `express_dynamic.c`.

Since `express_static.o` and `express_dynamic.o` both define the function `EXPRESSpass_3()`, only one is linked into any given executable. This selection is what determines whether a Fed-X translator links in output modules statically or dynamically. By default, the linkage mechanism will be `express_static.o`, which actually appears in the Working Form library. This choice can be overridden by placing `express_dynamic.o` before `libexpress.a` in the link command. Note that a suitable output module (`.o` file) must appear *after* `express_static.o` in the linker's argument list when a statically linked translator is being built. For more information on how to build a report generator into a Fed-X translator, see [Clark90c].

5 Working Form Routines

The remainder of this manual consists of specifications and brief descriptions of the access routines and associated error codes for the Express Working Form. The error codes are manipulated by the Error module [Clark90d]. Each subsection below corresponds to a module in the Working Form library. The Working Form Manager module is listed first, followed by the remaining data abstractions in alphabetical order.

5.1 Working Form Manager

Type: Express

Procedure: EXPRESSdump_model

Parameters: Express model - Express model to dump

Returns: void

Description: Dump an Express model to `stderr`. This call is provided for debugging purposes.

Procedure: EXPRESSfree

Parameters: Express model - Express model to free

Returns: void

Description: Release an Express model. Indicates that the model is no longer used by the caller; if there are no other references to the model, all storage associated with it may be released.

Procedure: EXPRESSinitialize

Parameters: -- none --

Returns: void

Description: Initialize the Express package. This call in turn initializes all components of the Working Form package. Normally, it is called instead of calling all of the individual `xxxinitialize()` routines. In a typical Express (or STEP) translator, this function is called by the default `main()` provided in the Working Form library. Other applications should call it at initialization time.

Procedure: EXPRESSpass_1
Parameters: FILE* file - Express source file to parse
Returns: Express - resulting Working Form model
Description: Parse an Express source file into the Working Form. No symbol resolution is performed

Procedure: EXPRESSpass_2
Parameters: Express model - Working Form model to resolve
Returns: void
Description: Perform symbol resolution on a loosely-coupled Working Form model (which was probably created by EXPRESSpass_1()).

Procedure: EXPRESSpass_3
Parameters: Express model - Working Form model to report
 FILE* file - output file
Returns: void
Description: Invoke one (or more) report generator(s), according to the selected linkage mechanism.

Procedure: PASS2initialize
Parameters: -- none --
Returns: void
Description: Initialize the Fed-X second pass.

5.2 Algorithm

Type: Algorithm
Supertype: Scope
Subtypes: Function, Procedure, Rule

Procedure: ALGget_body
Parameters: Algorithm algorithm - algorithm to examine
Returns: Linked_List - body of algorithm
Description: Retrieve the code body of an algorithm. The elements of the list returned are Statements.

Procedure: ALGget_name
Parameters: Algorithm algorithm - algorithm to examine
Returns: String - the name of the algorithm

Procedure: ALGget_parameters
Parameters: Algorithm algorithm - algorithm to examine
Returns: Linked_List - formal parameter list
Description: Retrieve the formal parameter list for an algorithm. When ALGget_class(algorithm) == ALG_RULE, the returned list contains the Entitys to which the rule applies. Otherwise, it contains Variables specifying the formal parameters to the function or procedure.

Procedure: ALGinitialize
Parameters: -- none --
Returns: void
Description: Initialize the Algorithm module. This is called by EXPRESSinitialize(), and so normally need not be called individually.

Procedure: ALGput_body
Parameters: Algorithm algorithm - algorithm to modify
 Linked_List statements - body of algorithm
Returns: void
Description: Set the code body of an algorithm. The second parameter should be a list of Statements.

Procedure: ALGput_name
Parameters: Algorithm algorithm - algorithm to modify
 String name - new name for algorithm
Returns: void
Description: Set the name of an algorithm.

Procedure: ALGput_parameters
Parameters: Algorithm algorithm - algorithm to modify
 Linked_List list - formal parameters for this algorithm
Returns: void
Description: Set the formal parameter list of an algorithm. When ALGget_class(algorithm) == ALG_RULE, the formal parameters should be the Entitys to which the rule applies. Otherwise, they should be Variables.

Procedure: ALGresolve
Parameters: Algorithm algorithm - algorithm to resolve
 Scope scope - scope in which to resolve
Returns: void
Description: Resolve all references in an algorithm definition. This is called, in due course, by EXPRESSpass_2().

Procedure: FUNCget_return_type
Parameters: Function function - function to examine
Returns: Type - function's return type

Procedure: FUNCput_return_type
Parameters: Function function - function to modify
 Type type - the function's return type
Returns: void
Description: Set the return type of a function.

Procedure: RULEget_where_clause
Parameters: Rule rule - rule to examine
Returns: Linked_List - list of rule's WHERE clause constraints

Procedure: RULEput_where_clause
Parameters: Rule rule - rule to modify
 Linked_List where - list of WHERE clause constraints for rule
Returns: void
Description: Set the where clause of a rule

5.3 Case Item

Type: Case_Item
Supertype: Construct

Procedure: CASE_ITcreate
Parameters: Linked_List of Expression labels - list of case labels
 Statement statement - statement associated with this branch
 Error* errc - buffer for error code
Returns: Case_Item - the case item created
Description: Create a new case item. If the 'labels' parameter is LIST_NULL, a case item matching in the default case is created. Otherwise, the case item created will match when the case selector has the same value as any of the Expressions on the labels list.
Errors: -- none --

Procedure: CASE_ITget_labels
Parameters: Case_Item item - case item to examine
Returns: Linked_List - list of case labels
Description: Retrieve the list of label Expressions for which a case item matches. For an item which matches in the default case, LIST_NULL is returned.

Procedure: CASE_ITget_statement
Parameters: Case_Item item - the case item to examine
Returns: Statement - statement associated with this branch
Description: Retrieve the statement to be executed when this case item is matched.

Procedure: CASE_ITinitialize
Parameters: -- none --
Returns: void
Description: Initialize the Case Item module. This is called by EXPRESSinitialize(), and so normally need not be called individually.

Procedure: CASE_ITresolve
Parameters: Case_Item item - case item to resolve
 Scope scope - scope in which to resolve
Returns: void
Description: Resolve all symbol references in a case item. This is called, in due course, by EXPRESSpass_2().

5.4 Constant

| | |
|---------------------|---|
| Type: | Constant |
| Supertype: | Symbol |
| Procedure: | CSTcreate |
| Parameters: | String name - name of new constant Type type - type of new constant Generic value - value for new constant |
| Returns: | Constant - the constant created |
| Description: | Create a new constant. |
| Procedure: | CSTget_name |
| Parameters: | Constant constant - constant to examine |
| Returns: | String - the name of the constant |
| Procedure: | CSTget_type |
| Parameters: | Constant constant - constant to examine |
| Returns: | Type - the type of the constant |
| Procedure: | CSTget_value |
| Parameters: | Constant constant - constant to examine |
| Returns: | Generic - the value of the constant |
| Procedure: | CSTinitialize |
| Parameters: | -- none -- |
| Returns: | void |
| Description: | Initialize the Constant module. This is called by <code>EXPRESSinitialize()</code> , and so normally need not be called individually. |
| Procedure: | CSTput_name |
| Parameters: | Constant constant - constant to modify String - name for constant |
| Returns: | void |
| Description: | Set the name of a constant |
| Procedure: | CSTput_type |
| Parameters: | Constant constant - constant to modify Type - type for constant |
| Returns: | void |
| Description: | Set the type of a constant |
| Procedure: | CSTput_value |
| Parameters: | Constant constant - constant to modify Generic - value of constant |
| Returns: | void |
| Description: | Set the value of a constant |

5.5 Construct

Type: Construct
Supertype: -- none --

Procedure: CONSTRget_line_number
Parameters: Construct construct - construct to examine
Returns: int - line number of construct

Procedure: CONSTRinitialize
Parameters: -- none --
Returns: void
Description: Initialize the Construct module. This is called by EXPRESSinitialize(), and so normally need not be called individually.

Procedure: CONSTRput_line_number
Parameters: Construct construct - construct to modify
 int number - line number for construct
Returns: void
Description: Set a construct's line number.

5.6 Entity

Type: Entity
Supertype: Scope

Procedure: ENTITYadd_attribute
Parameters: Entity entity - entity to modify
 Variable attribute - attribute to add
Returns: void

Procedure: ENTITYadd_instance
Parameters: Entity entity - entity to modify
 Generic instance - new instance
Returns: void

Procedure: ENTITYdelete_instance
Parameters: Entity entity - entity to modify
 Generic instance - instance to delete
Returns: void

Procedure: ENTITYget_all_attributes
Parameters: Entity entity - entity to examine
Returns: Linked_List of Variable - all attributes of this entity
Description: Retrieve the complete attribute list of an entity. The attributes are ordered as required by the STEP Physical File format [Altemeuller88]. This list should be LISTfree'd when no longer needed.

Procedure: ENTITYget_attribute_offset
Parameters: Entity entity - entity to examine
Variable attribute - attribute to retrieve offset for
Returns: int - offset to given attribute
Description: Retrieve offset to an entity attribute. This offset takes into account all superclass of the entity. It is computed by ENTITYget_initial_offset(entity) + VARget_offset(attribute). If the entity does not include the attribute, -1 is returned. This call should be preferred over ENTITYget_named_attribute_offset().

Procedure: ENTITYget_attributes
Parameters: Entity entity - entity to examine
Returns: Linked_List of Variable - local attributes of this entity
Description: Retrieve the local attribute list of an entity. The local attributes of an entity are those which are defined by the entity itself (rather than being inherited from supertypes). This list should be LISTfree'd when no longer needed.

Procedure: ENTITYget_constraints
Parameters: Entity entity - entity to examine
Returns: Linked_List of Expression - this entity's constraints
Description: Retrieve the list of constraints from an entity's "where" clause. This list should not be LISTfree'd.

Procedure: ENTITYget_initial_offset
Parameters: Entity entity - entity to examine
Returns: int - number of inherited attributes
Description: Retrieve the initial offset to an entity's local frame. This is the total number of explicit attributes inherited from supertypes.

Procedure: ENTITYget_instances
Parameters: Entity entity - entity to examine
Returns: Linked_List - list of instances of the entity
Description: Retrieve an entity's instance list. This list should not be LISTfree'd.

Procedure: ENTITYget_mark
Parameters: Entity entity - entity to examine
Returns: int - entity's current mark
Description: Retrieve an entity's mark. See ENTITYput_mark().

Procedure: ENTITYget_name
Parameters: Entity entity - entity to examine
Returns: String - entity name

Procedure: ENTITYget_named_attribute
Parameters: Entity entity - entity to examine
String name - name of attribute to retrieve
Returns: Variable - the named attribute of this entity
Description: Retrieve the definition of an entity attribute by name. If the entity has no attribute with the given name, VARIABLE_NULL is returned.

Procedure: ENTITYget_named_attribute_offset
Parameters: Entity entity - entity to examine
String name - name of attribute for which to retrieve offset
Returns: int - offset to named attribute of this entity
Description: Retrieve the offset to an entity attribute by name. If the entity has no attribute with the given name, -1 is returned. This call is slower than ENTITYget_attribute_offset(), and so should be avoided when the actual attribute definition is already available.

Procedure: ENTITYget_size
Parameters: Entity entity - entity to examine
Returns: int - storage size of instantiated entity
Description: Compute the storage size of an instantiation of this entity. This is the total number of attributes which it contains.

Procedure: ENTITYget_subtype_expression
Parameters: Entity entity - entity to examine
Returns: Expression - immediate subtype expression
Description: Retrieve the controlling expression for an entity's immediate subtype list.

Procedure: ENTITYget_subtypes
Parameters: Entity entity - entity to examine
Returns: Linked_List of Entity - immediate subtypes of this entity
Description: Retrieve a list of an entity's immediate subtypes.

Procedure: ENTITYget_supertypes
Parameters: Entity entity - entity to examine
Returns: Linked_List of Entity - immediate supertypes of this entity
Description: Retrieve a list of an entity's immediate supertypes. This list should not be LISTfree'd.

Procedure: ENTITYget_uniqueness_list
Parameters: Entity entity - entity to examine
Returns: Linked_List of Linked_List - this entity's uniqueness sets
Description: Retrieve an entity's uniqueness list. Each element of this list is itself a list of variables, specifying a uniqueness set for the entity. The uniqueness list should not be LISTfree'd, nor should any of the component lists.

Procedure: ENTITYhas_immediate_subtype
Parameters: Entity parent - entity to check children of
Entity child - child to check for
Returns: Boolean - is child a direct subtype of parent?

Procedure: ENTITYhas_immediate_supertype
Parameters: Entity child - entity to check parentage of
Entity parent - parent to check for
Returns: Boolean - is parent a direct supertype of child?

Procedure: ENTITYhas_subtype
Parameters: Entity parent - entity to check descendants of
Entity child - child to check for
Returns: Boolean - does parent's subclass tree include child?

Procedure: ENTITYhas_supertype
Parameters: Entity child - entity to check parentage of
Entity parent - parent to check for
Returns: Boolean - does child's superclass chain include parent?

Procedure: ENTITYinitialize
Parameters: -- none --
Returns: void
Description: Initialize the Entity module. This is called by EXPRESSinitialize(), and so normally need not be called individually.

Procedure: ENTITYput_constraints
Parameters: Entity entity - entity to modify
Linked_List constraints - list of constraints which entity must satisfy
Returns: void
Description: Set the constraints on an entity. The elements of the constraints list should be Expressions of type TY_LOGICAL.

Procedure: ENTITYput_inheritance_count
Parameters: Entity entity - entity to modify
int count - number of inherited attributes
Returns: void
Description: Set the number of attributes inherited by an entity. This should be computed automatically (perhaps only when needed), and this call removed. The count is currently computed by ENTITYresolve().

Procedure: ENTITYput_mark
Parameters: Entity entity - entity to modify
int value - new mark for entity
Returns: void
Description: Set an entity's mark. This mark is used, for example, in SCOPE_dfs(), part of SCOPEget_entities_superclass_order(), to mark each entity as having been touched by the traversal.

Procedure: ENTITYput_name
Parameters: Entity entity - entity to modify
String name - entity's name
Returns: void
Description: Set the name of an entity.

Procedure: ENTITYput_subtypes
Parameters: Entity entity - entity to modify
Expression expression - controlling subtype expression
Returns: void
Description: Set the (immediate) subtypes list of an entity.

Procedure: ENTITYput_supertypes
Parameters: Entity entity - entity to modify
Linked_List list - superclass entities
Returns: void
Description: Set the (immediate) supertype list of an entity. The elements of the list should be Entities or (unresolved) Symbols.

Procedure: ENTITYput_uniqueness_list
Parameters: Entity entity - entity to modify
 Linked_List list - uniqueness list
Returns: void
Description: Set the uniqueness list of an entity. Each element of the uniqueness list should itself be a list of Variables and/or (unresolved) Symbols referencing entity attributes. Each of these sublists specifies a single uniqueness set for the entity.

Procedure: ENTITYresolve
Parameters: Entity entity - entity to resolve
Returns: void
Description: Resolve all symbol references in an entity definition. This function is called, in due course, by EXPRESSpass_2().

5.7 Expression

Type: Expression
Supertype: Construct

Private Type: Ary_Expression
Supertype: Expression

Type: Binary_Expression
Supertype: Ary_Expression

Type: Unary_Expression
Supertype: Ary_Expression

Type: One_Of_Expression
Supertype: Expression

Type: Function_Call
Supertype: One_Of_Expression

Type: Identifier
Supertype: Expression

Private Type: Literal
Supertype: Expression

Type: Aggregate_Literal
Supertype: Literal

Type: Integer_Literal
Supertype: Literal

Type: Logical_Literal
Supertype: Literal

| | |
|---------------------|--|
| Type: | Real_Literal |
| Supertype: | Literal |
| | |
| Type: | String_Literal |
| Supertype: | Literal |
| | |
| Type: | Query |
| Supertype: | Expression |
| | |
| Constant: | LITERAL_EMPTY_SET - a generic set literal representing the empty set |
| Type: | Aggregate_Literal |
| | |
| Constant: | LITERAL_INFINITY - a numeric literal representing infinity |
| Type: | Integer_Literal |
| | |
| Constant: | LITERAL_PI - a real literal with the value 3.1415... |
| Type: | Real_Literal |
| | |
| Constant: | LITERAL_ZERO - an integer literal with the value 0 |
| Type: | Integer_Literal |
| | |
| Procedure: | AGGR_LITcreate |
| Parameters: | Type type - type of aggregate literal to be created Linked_List value - value for literal Error* errc - buffer for error code |
| Returns: | Aggregate_Literal - the literal created |
| Description: | Create an aggregate literal expression. |
| Errors: | -- none -- |
| | |
| Procedure: | AGGR_LITget_value |
| Parameters: | Aggregate_Literal literal - aggregate literal to examine Error* errc - buffer for error code |
| Returns: | Linked_List of Generic - the literal's contents |
| Description: | Retrieve the value of an aggregate literal, as a list. |
| Errors: | -- none -- |
| | |
| Procedure: | BIN_EXPcreate |
| Parameters: | Op_Code op - operation Expression operand1 - first operand Expression operand2 - second operand Error* errc - buffer for error code |
| Returns: | Binary_Expression - the expression created |
| Description: | Create a binary operation expression. |
| Errors: | -- none -- |
| | |
| Procedure: | BIN_EXPget_first_operand |
| Parameters: | Binary_Expression expression - expression to examine |
| Returns: | Expression - the first (left-hand) operand of the expression |

Procedure: BIN_EXPget_operator
Parameters: Binary_Expression expression - expression to examine
Returns: Op_Code - the operator invoked by the expression

Procedure: BIN_EXPget_second_operand
Parameters: Binary_Expression expression - expression to examine
Returns: Expression - the second (right-hand) operand of the expression

Procedure: EXPas_string
Parameters: Expression expression - expression to print as string
Returns: String - string representation of expression
Description: Generate the string representation of an expression. Only (qualified) identifiers are currently supported.

Procedure: EXPget_integer_value
Parameters: Expression expression - expression to evaluate
Error* errc - buffer for error code
Returns: int - value of expression
Description: Compute the value of an integer expression. Currently, only integer literals can be evaluated; other classes of expressions evaluate to 0 and produce a warning message. EXPRESSION_NULL evaluates to 0, as well.
Errors: ERROR_integer_expression_expected

Procedure: EXPget_type
Parameters: Expression expression - expression to examine
Returns: Type - the type of the value computed by the expression

Procedure: EXPinitialize
Parameters: -- none --
Returns: void
Description: Initialize the Expression module. This is called by EXPRESSinitialize(), and so normally need not be called individually.

Procedure: EXPput_type
Parameters: Expression expression - expression to modify
Type type - the type of result computed by the expression
Returns: void
Description: Set the type of an expression. This call should actually be unnecessary: the type of an expression is derivable from its definition. While this is currently true in the case of literals, there are no rules in place for deriving the type from, for example, the return type of a function or and operator together with its operands.

Procedure: EXPresolve
Parameters: Expression expression - expression to resolve
Scope scope - scope in which to resolve
Returns: void
Description: Resolve all symbol references in an expression. This is called, in due course, by EXPRESSpass_2().

Procedure: EXPresolve_qualification
Parameters: Expression expression - expression to resolve
Scope scope - scope in which to resolve
Error* errc - buffer for error code
Returns: Symbol - the symbol referenced by the expression
Description: Retrieves the symbol definition referenced by a (possibly qualified) identifier.

Procedure: FCALLcreate
Parameters: Algorithm algorithm - algorithm invoked by expression
Linked_List parameters - actual parameters to function call
Error* errc - buffer for error code
Returns: Function_Call - the function call created
Description: Create a function call expression.
Errors: -- none --

Procedure: FCALLget_algorithm
Parameters: Function_Call expression - function call expression to examine
Returns: Algorithm - the algorithm invoked by the function call

Procedure: FCALLget_parameters
Parameters: Function_Call expression - function call expression to examine
Returns: Linked_List of Expression - list of actual parameters
Description: Retrieve the actual parameter Expressions from a function call expression.

Procedure: FCALLput_algorithm
Parameters: Function_Call expression - function call expression to modify
Algorithm algorithm - algorithm invoked by expression
Returns: void
Description: Set the algorithm invoked by a function call expression.

Procedure: FCALLput_parameters
Parameters: Function_Call expression - function call expression to modify
Linked_List parameters - list of actual parameters
Returns: void
Description: Set the actual parameter list to a function call expression. The elements of the parameter list should be Expressions. The types of the actual parameters currently are not verified against the formal parameter list of the called algorithm.

Procedure: IDENTcreate
Parameters: Symbol ident - identifier referenced by expression
Error* errc - buffer for error code
Returns: Identifier - the identifier expression created
Description: Create a simple identifier expression.
Errors: -- none --

Procedure: IDENTget_identifier
Parameters: Identifier expression - expression to examine
Returns: Symbol - the identifier referenced in the expression

Procedure: IDENTput_identifier
Parameters: Identifier expression - identifier expression to modify
Symbol identifier - the referent of the identifier
Returns: void
Description: Set the referent of an identifier expression.

Procedure: INT_LITcreate
Parameters: Integer value - value for literal
Error* errc - buffer for error code
Returns: Integer_Literal - the literal created
Description: Create an integer literal expression.
Errors: -- none --

Procedure: INT_LITget_value
Parameters: Integer_Literal literal - integer literal to examine
Error* errc - buffer for error code
Returns: Integer - the literal's value
Errors: -- none --

Procedure: LOG_LITcreate
Parameters: Logical value - value for literal
Error* errc - buffer for error code
Returns: Logical_Literal - the literal created
Description: Create a logical literal expression.
Errors: -- none --

Procedure: LOG_LITget_value
Parameters: Logical_Literal literal - logical literal to examine
Error* errc - buffer for error code
Returns: Logical - the literal's value
Errors: -- none --

Procedure: ONEOFcreate
Parameters: Linked_List selections - list of selections for oneof()
Error* errc - buffer for error code
Returns: One_Of_Expression - the oneof expression created
Description: Create a oneof() expression.
Errors: -- none --

Procedure: ONEOFget_selections
Parameters: One_Of_Expression expression - expression to examine
Returns: Linked_List of Expression - list of selections for oneof()

Procedure: ONEOFput_selections
Parameters: One_Of_Expression expression - expression to modify
Linked_List selections - list of selections for oneof()
Returns: void
Description: Set the list of selections for a oneof() expression.

Procedure: OPget_number_of_operands
Parameters: Op_Code operation - the opcode to query
Returns: int - number of operands required by this operator.

Procedure: QUERYcreate
Parameters: String ident - local identifier for source elements
Expression source - source aggregate to query
Expression discriminant - discriminating expression for query
Error* errc - buffer for error code
Returns: Query - the query expression created
Description: Create a query expression.
Errors: -- none --

Procedure: QUERYget_discriminant
Parameters: Query expression - query expression to examine
Returns: Expression - the discriminant expression
Description: Retrieves the discriminant expression from a query expression. The discriminant expresses the query criteria.

Procedure: QUERYget_source
Parameters: Query expression - query expression to examine
Returns: Expression - the source aggregation
Description: Retrieves the expression which computes the aggregation against which a query will be applied.

Procedure: QUERYget_variable
Parameters: Query expression - query expression to examine
Returns: Variable - the local iteration variable of the query

Procedure: REAL_LITcreate
Parameters: Real value - value for literal
Error* errc - buffer for error code
Returns: Real_Literal - the literal created
Description: Create a real literal expression.
Errors: -- none --

Procedure: REAL_LITget_value
Parameters: Real_Literal literal - real literal to examine
Error* errc - buffer for error code
Returns: Real - the literal's value
Errors: -- none --

Procedure: STR_LITcreate
Parameters: String value - value for literal
Error* errc - buffer for error code
Returns: String_Literal - the literal created
Description: Create a string literal expression.
Errors: -- none --

Procedure: STR_LITget_value
Parameters: String_Literal literal - string literal to examine
Error* errc - buffer for error code
Returns: String - the literal's value
Errors: -- none --

Procedure: UN_EXPcreate
Parameters: Op_Code op - operation
Expression operand - operand
Error* errc - buffer for error code
Returns: Unary_Expression - the expression created
Description: Create a unary operation expression.
Errors: -- none --

Procedure: UN_EXPget_operand
Parameters: Unary_Expression expression - expression to examine
Returns: Expression - the operand of the expression

Procedure: UN_EXPget_operator
Parameters: Unary_Expression expression - expression to examine
Returns: Op_Code - the operator invoked by the expression

5.8 Loop Control

Type: Loop_Control
Supertype: Construct

Type: Increment_Control
Supertype: Loop_Control

Private Type: Conditional_Control
Supertype: Loop_Control

Type: Until_Control
Supertype: Conditional_Control

Type: While_Control
Supertype: Conditional_Control

Procedure: INCR_CTLcreate
Parameters: Expression control - controlling expression
Expression start - initial value
Expression end - terminal value
Expression increment - amount by which to increment
Error* errc - buffer for error code
Returns: Increment_Control - the loop control created
Errors: -- none --

Procedure: UNTILcreate
Parameters: Expression control - termination condition
Error* errc - buffer for error code
Returns: Until - the loop control created
Requires: OBJis_kind_of(EXPget_type(control), Class_Logical_Type)
Errors: ERROR_control_boolean_expected - controlling expression is not logical

Procedure: WHILEcreate
Parameters: Expression control - continuation condition
Error* errc - buffer for error code
Returns: While - the loop control created
Requires: OBJis_kind_of(EXPget_type(control), Class_Logical_Type)
Errors: ERROR_control_boolean_expected - controlling expression is not logical

Procedure: LOOP_CTLget_controlling_expression
Parameters: Loop_Control control - loop control to examine
Returns: Expression - controlling expression
Description: Retrieve a loop control's controlling expression. For while and until controls, this is the termination or continuation condition, respectively. For iteration and set scan controls, this is the expression which receives successive values in the iteration.

Procedure: INCR_CTLget_final
Parameters: Increment_Control control - increment control to examine
Returns: Expression - terminal value for controlling expression
Description: Retrieve the final value from an increment control.

Procedure: INCR_CTLget_increment
Parameters: Increment_Control control - increment control to examine
Returns: Expression - amount to increment by on each iteration
Description: Retrieve the increment expression from an increment control.

Procedure: INCR_CTLget_start
Parameters: Increment_Control control - increment control to examine
Returns: Expression - initial expression for controlling expression
Description: Retrieve the initial value from an increment control.

Procedure: LOOP_CTLinitialize
Parameters: -- none --
Returns: void
Description: Initialize the Loop Control module. This is called by EXPRESSinitialize(), and so normally need not be called individually.

Procedure: LOOP_CTLresolve
Parameters: Loop_Control control - control to resolve
Scope scope - scope in which to resolve
Returns: void
Description: Resolve all symbol references in a loop control. This is called, in due course, by EXPRESSpass_2().

5.9 Schema

| | |
|---------------------|---|
| Type: | Schema |
| Supertype: | Scope |
| Procedure: | SCHEMAcreate |
| Parameters: | String name - name of schema to create Scope scope - local scope for schema Error* errc - buffer for error code |
| Returns: | Schema - the schema created |
| Description: | Create a new schema. |
| Procedure: | SCHEMAdump |
| Parameters: | Schema schema - schema to dump FILE* file - file to dump to |
| Returns: | void |
| Description: | Dump a schema to a file. This function is provided for debugging purposes. |
| Procedure: | SCHEMAget_name |
| Parameters: | Schema schema - schema to examine |
| Returns: | String - the schema's name |
| Procedure: | SCHEMAinitialize |
| Parameters: | -- none -- |
| Returns: | void |
| Description: | Initialize the Schema module. This is called by EXPRESSinitialize(), and so normally need not be called individually. |
| Procedure: | SCHEMAresolve |
| Parameters: | Schema schema - schema to resolve |
| Returns: | void |
| Description: | Resolve all symbol references within a schema. In order to avoid problems due to references to as-yet-unresolved symbols, schema resolution is broken into two passes, which are implemented by SCHEMAresolve_pass1() and SCHEMAresolve_pass2(). These two are called in turn by SCHEMAresolve(). |

5.10 Scope

| | |
|---------------------|--|
| Type: | Scope |
| Supertype: | Symbol |
| Procedure: | SCOPEadd_import |
| Parameters: | Scope scope - scope to modify Symbol schema - schema to import (assume) |
| Returns: | void |
| Description: | Add a schema to the import list of a scope. If the symbol given has not been resolved to a schema, SCOPEresolve() will see to it that it is. |

Procedure: SCOPEadd_private
Parameters: Scope scope - scope to modify
Symbol name - item to add to private list
Returns: void
Description: Add an item to a scope's list of private declarations.

Procedure: SCOPEadd_superscope
Parameters: Scope scope - scope to modify
Scope parent - additional parent scope
Returns: void
Description: Add an immediate parent to a scope.

Procedure: SCOPEcreate
Parameters: Scope scope - next higher scope
Returns: Scope - the scope created
Description: Create an empty scope. Note that the connection between this new scope and its parent (the sole parameter to this call) is uni-directional: the parent does not immediately know about the child.

Procedure: SCOPEdefine_symbol
Parameters: Scope scope - scope in which to define symbol
Symbol symdef - new symbol definition
Error* errc - buffer for error code
Returns: void
Description: Define a symbol in a scope.
Errors: Reports all errors directly, so only ERROR_subordinate_failed is propagated.

Procedure: SCOPEdump
Parameters: Scope scope - scope to dump
FILE* file - file stream to dump to
Returns: void
Description: Dump a schema to a file. This function is provided for debugging purposes.

Procedure: SCOPEget_algorithms
Parameters: Scope scope - scope to examine
Returns: Linked_List - list of locally defined algorithms
Description: Retrieve a list of the algorithms defined locally in a scope. The elements of this list are Algorithms. The list should be LISTfree'd when no longer needed.

Procedure: SCOPEget_constants
Parameters: Scope scope - scope to examine
Returns: Linked_List - list of locally defined constants
Description: Retrieve a list of the constants defined locally in a scope. The elements of this list are Constants. The list should be LISTfree'd when no longer needed.

Procedure: SCOPEget_entities
Parameters: Scope scope - scope to examine
Returns: Linked_List - list of locally defined entities
Description: Retrieve a list of the entities defined locally in a scope. The elements of this list are Entities. The list should be LISTfree'd when no longer needed. This function is considerably faster than SCOPEget_entities_superclass_order(), and should be used whenever the order of the entities on the list is not important.

| | |
|---------------------|---|
| Procedure: | SCOPEget_entities_superclass_order |
| Parameters: | Scope scope - scope to examine |
| Returns: | Linked_List - list of locally defined entities in superclass order |
| Description: | Retrieve a list of the entities defined locally in a scope. The elements of this list are Entities. The list should be LISTfree'd when no longer needed. The list returned is ordered such that each entity appears before all of its subtypes. |
| Procedure: | SCOPEget_imports |
| Parameters: | Scope scope - scope to examine |
| Returns: | Linked_List - 'assumed' schemata |
| Description: | Retrieve a list of the schemata assumed in a scope. The elements of this list are Schemas. The list should <u>not</u> be LISTfree'd. |
| Procedure: | SCOPEget_resolved |
| Parameters: | Scope scope - scope to examine |
| Returns: | Boolean - has this scope been resolved? |
| Description: | Check whether symbol references in a scope have been resolved. |
| Procedure: | SCOPEget_schemata |
| Parameters: | Scope scope - scope to examine |
| Returns: | Linked_List - list of locally defined schemata |
| Description: | Retrieve a list of the schemata defined locally in a scope. The elements of this list are Schemas. The list should be LISTfree'd when no longer needed. |
| Procedure: | SCOPEget_superscopes |
| Parameters: | Scope scope - scope to examine |
| Returns: | Linked_List - list of next outer (containing) scopes |
| Description: | Retrieve a list of a scope's parent scope. |
| Procedure: | SCOPEget_types |
| Parameters: | Scope scope - scope to examine |
| Returns: | Linked_List - list of locally defined types |
| Description: | Retrieve a list of the types defined locally in a scope. The elements of this list are Types. The list should be LISTfree'd when no longer needed. |
| Procedure: | SCOPEget_variables |
| Parameters: | Scope scope - scope to examine |
| Returns: | Linked_List - list of locally defined variables |
| Description: | Retrieve a list of the variables defined locally in a scope. The elements of this list are Variables. The list should be LISTfree'd when no longer needed. |
| Procedure: | SCOPEinitialize |
| Parameters: | -- none -- |
| Returns: | void |
| Description: | Initialize the Scope module. This is called by EXPRESSinitialize(), and so normally need not be called individually. |

| | |
|---------------------|--|
| Procedure: | SCOPElookup |
| Parameters: | Scope scope - scope in which to look up name String name - name to look up Boolean walk - look in parent and imported scopes? Error* errc - buffer for error code |
| Returns: | Symbol - definition of name in scope |
| Description: | Retrieve a name's definition in a scope. If the scope does not define the name, the parent scopes are successively queried. If no definition is found, SYMBOL_NULL is returned. |
| Errors: | ERROR_undefined_identifier - no definition was found |
| Procedure: | SCOPEput_imports |
| Parameters: | Scope scope - scope to modify Linked_List imports - list of schemata to assume |
| Returns: | void |
| Description: | Set the entire list of assumed schemata in one fell swoop. |
| Procedure: | SCOPEput_resolved |
| Parameters: | Scope scope - scope to modify |
| Returns: | void |
| Description: | Set the 'resolved' flag for a scope. This normally should only be called by SCOPEresolve(), which actually resolves the scope. |
| Procedure: | SCOPEresolve |
| Parameters: | Scope scope - scope to resolve |
| Returns: | void |
| Description: | Resolve all symbol references in a scope. In order to avoid problems due to references to as-yet-unresolved symbols, scope resolution is broken into two passes, which are implemented by SCOPEresolve_pass1() and SCOPEresolve_pass2(). These two are called in turn by SCOPEresolve(). |

5.11 Statement

| | |
|----------------------|--------------------|
| Private Type: | Statement |
| Supertype: | Construct |
| Type: | Assignment |
| Supertype: | Statement |
| Type: | Compound_Statement |
| Supertype: | Statement |
| Type: | Conditional |
| Supertype: | Statement |
| Type: | Loop |
| Supertype: | Statement |
| Type: | Procedure_Call |
| Supertype: | Statement |

| | |
|---------------------|--|
| Type: | Return_Statement |
| Supertype: | Statement |
| Type: | With_Statement |
| Supertype: | Statement |
| Procedure: | ASSIGNcreate |
| Parameters: | Expression lhs - the left-hand-side of the assignment Expression rhs - the right-hand-side of the assignment Error* errc - buffer for error code |
| Returns: | Assignment - the assignment statement created |
| Description: | Create an assignment statement. |
| Procedure: | ASSIGNget_lhs |
| Parameters: | Assignment statement - statement to examine |
| Returns: | Expression - left-hand-side of assignment statement |
| Procedure: | ASSIGNget_rhs |
| Parameters: | Assignment statement - statement to examine |
| Returns: | Expression - right-hand-side of assignment statement |
| Procedure: | CASEcreate |
| Parameters: | Expression selector - expression to case on Linked_List case - list of case branches Error* errc - buffer for error code |
| Returns: | Case_Statement - the case statement created |
| Description: | Create a case statement. The elements of the case branch list should be Case_Items. |
| Procedure: | CASEget_items |
| Parameters: | Case_Statement statement - statement to examine |
| Returns: | Linked_List - case branches |
| Description: | Retrieve a list of the branches in a case statement. The elements of this list are Case_Items. |
| Procedure: | CASEget_selector |
| Parameters: | Case_Statement statement - statement to examine |
| Returns: | Expression - the selector for the case statment |
| Description: | Retrieve the selector from a case statement. This is the expression whose value is compared to each case label in turn. |
| Procedure: | COMP_STMTcreate |
| Parameters: | Linked_List statements - list of compound statement elements Error* errc - buffer for error code |
| Returns: | Compound_Statement - the compound statement created |
| Description: | Create a compound statement. The elements of the statements list should be Statements, in the order they appear in the compound statement to be represented. |
| Procedure: | COMP_STMTget_items |
| Parameters: | Compound_Statement statement - statement to examine |
| Returns: | Linked_List - list of statements in compound |
| Description: | Retrieve a list of the Statements comprising a compound statement. |

Procedure: CONDcreate
Parameters: Expression test - the condition for the if
Statement then - code executed when test == true
Statement otherwise - code executed when test == false
Error* errc - buffer for error code
Returns: Conditional - the if statement created
Description: Create an if statement. For a simple if . . then . . with no else clause, set the third parameter to STATEMENT_NULL.

Procedure: CONDget_else_clause
Parameters: Conditional statement - statement to examine
Returns: Statement - code for 'else' branch

Procedure: CONDget_condition
Parameters: Conditional statement - statement to examine
Returns: Expression - the test condition

Procedure: CONDget_then_clause
Parameters: Conditional statement - statement to examine
Returns: Statement - code for 'then' branch

Procedure: LOOPcreate
Parameters: Linked_List controls - list of controls for the loop
Statement body - statement to be repeated
Error* errc - buffer for error code
Returns: Loop - the loop statement created
Description: Create a loop statement. The elements of the controls list should be Loop_Controls.

Procedure: LOOPget_body
Parameters: Loop statement - statement to examine
Returns: Statement - the body of the loop
Description: Retrieve the body (repeated portion) of a loop statement

Procedure: LOOPget_controls
Parameters: Loop statement - statement to examine
Returns: Linked_List - list of loop controls
Description: Retrieve a list of a loop statement's controls. The elements of this list are Loop_Controls.

Procedure: PCALLcreate
Parameters: Procedure procedure - procedure called by statement
Linked_List parameters - list of actual parameters
Error* errc - buffer for error code
Returns: Procedure_Call - the procedure call created
Description: Create a procedure call statement. The elements of the actual parameter list should be Expressions which compute the values to be passed to the procedure.

| | |
|---------------------|---|
| Procedure: | PCALLget_procedure |
| Parameters: | Procedure_Call statement - statement to examine |
| Returns: | Procedure - procedure called by this statement |
| Description: | Retrieve the procedure called by a procedure call statement. |
| Procedure: | PCALLget_parameters |
| Parameters: | Procedure_Call statement - statement to examine |
| Returns: | Linked_List - actual parameters to this call |
| Description: | Retrieve the actual parameters for a procedure call statement. The elements of this list are Expressions which compute the values to be passed to the called routine. |
| Procedure: | PCALLput_procedure |
| Parameters: | Procedure_Call statement - statement to modify Procedure procedure - definition of called procedure |
| Returns: | void |
| Description: | Set the actual procedure called by a procedure call statement. If a procedure stub (unresolved Symbol) is present in the statement, it is replaced such that all references remain valid. |
| Procedure: | RETcreate |
| Parameters: | Expression expression - expression to compute return value Error* errc - buffer for error code |
| Returns: | Return_Statement - the return statement created |
| Description: | Create a return statement. |
| Procedure: | RETget_expression |
| Parameters: | Return_Statement statement - statement to examine |
| Returns: | Expression - expression returned by this statement |
| Description: | Retrieve the expression whose value is computed and returned by a return statement. |
| Procedure: | STMTinitialize |
| Parameters: | -- none -- |
| Returns: | void |
| Description: | Initialize the Statement module. This is called by EXPRESSinitialize(), and so normally need not be called individually. |
| Procedure: | STMTresolve |
| Parameters: | Statement statement - statement to resolve Scope scope - scope in which to resolve |
| Returns: | void |
| Description: | Resolve all symbol references in a statement. This is called, in due course, by EXPRESSpass_2(). |
| Procedure: | WITHcreate |
| Parameters: | Expression expression - controlling expression for the with Statement body - controlled statement for the with Error* errc - buffer for error code |
| Returns: | With_Statement - the with statement created |
| Description: | Create a with statement. |

Procedure: WITHget_body
Parameters: With_Statement statement - statement to examine
Returns: Statement - statement forming the body of the with statement

Procedure: WITHget_control
Parameters: With_Statement statement - statement to examine
Returns: Expression - the controlling expression
Description: Retrieve the controlling expression from a with statement. This is the expression which will be prepended to any expression which cannot otherwise be evaluated in the current scope.

5.12 Symbol

Type: Symbol
Supertype: -- none --

Procedure: SYMBOLget_line_number
Parameters: Symbol symbol - symbol to examine
Returns: int - line number of symbol

Procedure: SYMBOLget_name
Parameters: Symbol symbol - symbol to examine
Returns: String - name of symbol

Procedure: SYMBOLget_resolved
Parameters: Symbol symbol - symbol to examine
Returns: Boolean - is the symbol resolved?
Description: Test whether a symbol has been resolved.

Procedure: SYMBOLinitialize
Parameters: -- none --
Returns: void
Description: Initialize the Symbol module. This is called by EXPRESSinitialize(), and so normally need not be called individually.

Procedure: SYMBOLput_line_number
Parameters: Symbol symbol - symbol to modify
 int number - line number for symbol
Returns: void
Description: Set a symbol's line number.

Procedure: SYMBOLput_name
Parameters: Symbol symbol - symbol to name
 String name - name of symbol
Returns: void
Description: Set the name of a symbol.

Procedure: SYMBOLput_resolved
Parameters: Symbol symbol - symbol to mark resolved
Returns: void
Description: Mark a symbol as being resolved. This is normally called by the client
 XXXput_resolved() functions, since a symbol cannot itself be resolved.

5.13 Type

Private Type: Type
Supertype: Symbol

Type: Aggregate_Type
Supertype: Type

Type: Array_Type
Supertype: Aggregate_Type

Type: Bag_Type
Supertype: Aggregate_Type

Type: List_Type
Supertype: Aggregate_Type

Type: Set_Type
Supertype: Aggregate_Type

Private Type: Composed_Type
Supertype: Type

Type: Entity_Type
Supertype: Composed_Type

Type: Enumeration_Type
Supertype: Composed_Type

Type: Select_Type
Supertype: Composed_Type

Type: Generic_Type
Supertype: Type

Type: Logical_Type
Supertype: Type

Type: Boolean_Type
Supertype: Logical_Type

Type: Number_Type
Supertype: Type

| | |
|----------------------|--|
| Private Type: | Sized_Type |
| Supertype: | Type |
| Type: | Integer_Type |
| Supertype: | Sized_Type |
| Type: | Real_Type |
| Supertype: | Sized_Type |
| Type: | String_Type |
| Supertype: | Sized_Type |
| Type: | Type_Reference |
| Supertype: | Type |
| Constant: | TYPE_AGGREGATE |
| Description: | Type for general aggregate of generic. |
| Constant: | TYPE_BOOLEAN |
| Description: | Boolean type. |
| Constant: | TYPE_GENERIC |
| Description: | The type 'generic.' |
| Constant: | TYPE_INTEGER |
| Description: | Integer type with default precision. |
| Constant: | TYPE_LOGICAL |
| Description: | Logical type. |
| Constant: | TYPE_META |
| Description: | Meta type (for TYPEOF expressions). |
| Constant: | TYPE_NUMBER |
| Description: | Number type. |
| Constant: | TYPE_REAL |
| Description: | Real type with default precision. |
| Constant: | TYPE_SET_OF_GENERIC |
| Description: | Type for unconstrained set of generic. |
| Constant: | TYPE_STRING |
| Description: | String type with default precision (length). |

| | |
|---------------------|---|
| Procedure: | AGGR_TYPEget_optional |
| Parameters: | Aggregate_Type type - type to examine |
| Returns: | Boolean - are elements of this aggregate optional? |
| Description: | Retrieve the 'optional' flag from an aggregate type. This flag is true if and only if a legal instantiation of the type need not have all of its slots filled. |
| Procedure: | AGGR_TYPEget_unique |
| Parameters: | Aggregate_Type type - type to examine |
| Returns: | Boolean - must elements of this aggregate be unique? |
| Description: | Retrieve the 'unique' flag from an aggregate type. This flag is true if and only if a legal instantiation of the type may not contain duplicates. |
| Procedure: | AGGR_TYPEget_base_type |
| Parameters: | Aggregate_Type type - type to examine |
| Returns: | Type - the base type of the aggregate type |
| Description: | Retrieve the base type of an aggregate. This is the type of each element of an instantiation of the type. |
| Procedure: | AGGR_TYPEget_lower_limit |
| Parameters: | Aggregate_Type type - type to examine |
| Returns: | Expression - lower limit of the aggregate type |
| Description: | Retrieve an aggregate type's lower bound. For an array type, this is the lowest index; for other aggregate types, it specifies the minimum number of elements which the aggregate must contain. |
| Procedure: | AGGR_TYPEget_upper_limit |
| Parameters: | Aggregate_Type type - type to examine |
| Returns: | Expression - upper limit of the aggregate type |
| Description: | Retrieve an aggregate type's upper bound. For an array type, this is the high index; for other aggregate types, it specifies the maximum number of elements which the aggregate may contain. |
| Procedure: | AGGR_TYPEput_optional |
| Parameters: | Aggregate_Type type - type to modify Boolean optional - are array elements optional? |
| Returns: | void |
| Description: | Set the 'optional' flag for an array type. This flag indicates that all slots in an instance of the type need not be filled. |
| Procedure: | AGGR_TYPEput_unique |
| Parameters: | Aggregate_Type type - type to modify Boolean unique - are aggregate elements required to be unique? |
| Returns: | void |
| Description: | Set the 'unique' flag for an aggregate type. This flag indicates that an instantiation of the type may not contain duplicate items. |
| Procedure: | AGGR_TYPEput_base_type |
| Parameters: | Aggregate_Type type - type to modify Type base - the base type for this aggregate |
| Returns: | void |
| Description: | Set the base type of an aggregate type. This is the type of every element. |

Procedure: AGGR_TYPEput_limits
Parameters: Aggregate_Type type - type to modify
Expression lower - lower bound for aggregate
Expression upper - upper bound for aggregate
Returns: void
Description: Set the lower and upper bounds for an aggregate type. For an array type, these are the low and high indices; for other aggregates, the specify the minimum and maximum number of elements which an instance may contain.

Procedure: ENT_TYPEget_entity
Parameters: Entity_Type type - type to examine
Returns: Entity - definition of entity type
Description: Retrieve the (first) entity referenced by an entity type.

Procedure: ENT_TYPEget_entity_list
Parameters: Entity_Type type - type to examine
Returns: Linked_List - definition of entity type
Description: Retrieve a list of the entities referenced by an entity type.

Procedure: ENT_TYPEput_entity
Parameters: Entity_Type type - type to modify
Entity entity - definition of type
Returns: void
Description: Set the entity referred to by an entity type.

Procedure: ENT_TYPEput_entity_list
Parameters: Entity_Type type - type to modify
Linked_List - definition of type
Returns: void
Description: Set the list of entities referred to by an entity type.

Procedure: ENUM_TYPEget_items
Parameters: Enumeration_Type type - type to examine
Returns: Linked_List - list of enumeration items
Description: Retrieve an enumerated type's list of identifiers. Each element of this list is a Constant.

Procedure: ENUM_TYPEput_items
Parameters: Enumeration_Type type - type to modify
Linked_List list - list of enumeration items
Returns: void
Description: Set the list of identifiers for an enumerated type. Each element of this list should be a Constant.

Procedure: SEL_TYPEget_items
Parameters: Select_Type type - type to examine
Returns: Linked_List - list of selectable types
Description: Retrieve a list of the selectable types from a select type.

| | |
|---------------------|---|
| Procedure: | SEL_TYPEput_items |
| Parameters: | Select_Type type - type to modify Linked_List list - list of selectable types |
| Returns: | void |
| Description: | Set the list of selections for a select type. An instance of any these types is a legal instantiation of the select type. Each Type on the list should be of class TYPE_ENTITY or TYPE_SELECT. |
| Procedure: | SZD_TYPEget_precision |
| Parameters: | Sized_Type type - type to examine |
| Returns: | Expression - the precision specification of the type |
| Description: | Retrieve the precision specification from certain types. This specifies the maximum number of significant digits or characters in an instance of the type. |
| Procedure: | SZD_TYPEget_varying |
| Parameters: | Sized_Type type - type to examine |
| Returns: | Boolean - is the string type of varying length? |
| Description: | Retrieve the 'varying' flag from a string type. This flag is true if and only if the length of an instance may vary, up to the type's precision. It is true by default. |
| Procedure: | SZD_TYPEput_precision |
| Parameters: | Sized_Type type - type to modify Expression prec - the precision of the type |
| Returns: | void |
| Description: | Set the precision of certain types. This is the maximum number of significant digits or characters in an instance. |
| Procedure: | SZD_TYPEput_varying |
| Parameters: | Sized_Type type - type to modify Boolean varying - is string type of varying length? |
| Returns: | void |
| Description: | Set the 'varying' flag of a string type. This flag indicates that the length of an instance may vary, up to the type's precision. The default behavior for a string type is to be varying, i.e., strings are initialized as if TYPEput_varying(string, true) were called. |
| Procedure: | TYPEcompatible |
| Parameters: | Type lhs_type - type for left-hand-side of assignment Type rhs_type - type for right-hand-side of assignment |
| Returns: | Boolean - are the types assignment compatible? |
| Description: | Determine whether two types are assignment-compatible. It must be possible to assign a value of rhs_type into a slot of lhs_type. |
| Procedure: | TYPEget_name |
| Parameters: | Type type - type to examine |
| Returns: | String - the name of the type |

Procedure: TYPEget_size
Parameters: Type type - type to examine
Returns: int - logical size of a type instance
Description: Compute the size of an instance of some type. Simple types all have size 1, as does a select type. The size of an aggregate type is the maximum number of elements an instance can contain; and the size of an entity type is its total attribute count. If an aggregate type is unbounded, the constant TYPE_UNBOUNDED_SIZE is returned. This value may be ambiguous; the upper bound of the type should be relied on to determined unboundedness. It is intended that the initial memory allocation for such an aggregate should give space for TYPE_UNBOUNDED_SIZE elements, and that this should grow as needed. By returning some reasonable initial size, this call allows its return value to be used immediately as a parameter to a memory allocator, without being checked for validity. This is the approach taken in the STEP Working Form [Clark90d], [Clark90e].

Procedure: TYPEget_where_clause
Parameters: Type type - type to examine
Returns: Linked_List - the type's WHERE clause
Description: Retrieve the WHERE clause associated with a type. Each element of the returned list will be an Expression which computes a Logical result.

Procedure: TYPEinitialize
Parameters: -- none --
Returns: void
Description: Initialize the Type module. This is called by EXPRESSinitialize(), and so normally need not be called individually.

Procedure: TYPEput_name
Parameters: Type type - type to modify
String name - new name for type
Returns: void
Description: Set the name of a type.

Procedure: TYPEput_where_clause
Parameters: Type type - type to modify
Linked_List - the type's WHERE clause
Returns: void
Description: Set the WHERE clause associated with a type. Each element of the list should be an Expression which computes a Logical result.

Procedure: TYPEresolve
Parameters: Type type - type to resolve
Scope scope - scope in which to resolve
Returns: void
Description: Resolve all references in a type definition, and transform a type reference into the appropriate Type or Entity construct. This is called, in due course, by EXPRESSpass_2().

Procedure: TYPE_REFget_full_name
Parameters: Type_Reference type - type reference to examine
Returns: Expression - [qualified] identifier expression for type reference
Description: Retrieve the identifier expression for a type reference. This expression consists of identifier components assembled into binary expressions with OP_DOT.

Procedure: TYPE_REFput_full_name
Parameters: Type_Reference type - type reference to modify
 Expression name - [qualified] identifier expression for type reference
Returns: void
Description: Set the identifier expression for a type reference.

5.14 Variable

Type: Variable
Supertype: Symbol

Procedure: VARcreate
Parameters: String name - name of variable to create
 Type type - type of variable to create
 Error* errc - buffer for error code
Returns: Variable - the Variable created
Description: Create a new variable. The reference class of the variable is, by default, REF_DYNAMIC. All special flags associated with the variable (e.g., optional) are initially false.

Procedure: VARget_derived
Parameters: Variable var - variable to examine
Returns: Boolean - value of variable's derived flag
Description: Retrieve the value of a variable's 'derived' flag. This flag indicates that an entity attribute's value should always be computed by its initializer; no value will ever be specified for it.

Procedure: VARget_initializer
Parameters: Variable var - variable to modify
Returns: Expression - variable initializer
Description: Retrieve the expression used to initialize a variable.

Procedure: VARget_name
Parameters: Variable var - variable to examine
Returns: String - the name of the variable

Procedure: VARget_offset
Parameters: Variable var - variable to examine
Returns: int - offset to variable in local frame
Description: Retrieve the offset to a variable in its local frame. This offset alone is not sufficient in the case of an entity attribute (see ENTITYget_attribute_offset()).

Procedure: VARget_optional
Parameters: Variable var - variable to examine
Returns: Boolean - value of variable's optional flag
Description: Retrieve the value of a variable's 'optional' flag. This flag indicates that a particular entity attribute need not have a value when the entity is instantiated.

Procedure: VARget_reference_class
Parameters: Variable var - variable to examine
Returns: Reference_Class - the variable's reference class

Procedure: VARget_type
Parameters: Variable var - variable to examine
Returns: Type - the type of the variable

Procedure: VARget_variable
Parameters: Variable var - variable to examine
Returns: Boolean - value of variable's variable flag
Description: Retrieve the value of a variable's 'variable' flag. This flag indicates that an algorithm parameter is to be passed by reference, so that it can be modified by the callee.

Procedure: VARinitialize
Parameters: -- none --
Returns: void
Description: Initialize the Variable module. This is called by EXPRESSinitialize(), and so normally need not be called individually.

Procedure: VARput_derived
Parameters: Variable var - variable to modify
 Boolean val - new value for derived flag
Returns: void
Description: Set the value of the 'derived' flag for a variable. This flag is currently redundant, as a derived attribute can be identified by the fact that it has an initializing expression. This may not always be true, however.

Procedure: VARput_initializer
Parameters: Variable var - variable to modify
 Expression init - initializer
Returns: void
Description: Set the initializing expression for a variable.

Procedure: VARput_offset
Parameters: Variable var - variable to modify
 int offset - offset to variable in local frame
Returns: void
Description: Set a variable's offset in its local frame. Note that in the case of an entity attribute, this offset is *from the first locally defined attribute*, and must be used in conjunction with entity's initial offset (see ENTITYget_attribute_offset()).

Procedure: VARput_optional
Parameters: Variable var - variable to modify
 Boolean val - value for optional flag
Returns: void
Description: Set the value of the 'optional' flag for a variable. This flag indicates that a particular entity attribute need not have a value when the entity is instantiated. It is initially false.

Procedure: VARput_reference_class
Parameters: Variable var - variable to modify
 Reference_Class ref - the variable's reference class
Returns: void
Description: Set the reference class of a variable. The reference class defaults to REF_DYNAMIC.

Procedure: VARput_variable
Parameters: Variable var - variable to modify
 Boolean val - new value for variable flag
Returns: void
Description: Set the value of the 'variable' flag for a variable. This flag indicates that an algorithm parameter is to be passed by reference, so that it can be modified by the callee.

Procedure: VARresolve
Parameters: Variable variable - variable to resolve
 Scope scope - scope in which to resolve
Returns: void
Description: Resolve all symbol references in a variable definition. This is called, in due course, by EXPRESSpass_2().

6 Express Working Form Error Codes

The Error module, which is used to manipulate these error codes, is described in [Clark90c].

Error: ERROR_bail_out
Defined In: Express
Severity: SEVERITY_DUMP
Meaning: Fed-X internal error
Format: -- none --

Error: ERROR_control_boolean_expected
Defined In: Loop_Control
Severity: SEVERITY_WARNING
Meaning: The controlling expression for a while or until does not seem to return boolean. In the current implementation, this message can be erroneously produced because proper types are not derived for complex expressions; thus, an expression which truly does compute a boolean result may not appear to do so according to the Working Form.
Format: -- none --

Error: ERROR_corrupted_expression
Defined In: Expression
Severity: SEVERITY_DUMP
Meaning: Fed-X internal error: an Expression structure was corrupted
Format: %s - function detecting error

Error: ERROR_corrupted_statement
Defined In: Statement
Severity: SEVERITY_DUMP
Meaning: Fed-X internal error: a Statement structure was corrupted
Format: %s - function detecting error

| | |
|--------------------|---|
| Error: | ERROR_corrupted_type |
| Defined In: | Type |
| Severity: | SEVERITY_DUMP |
| Meaning: | Fed-X internal error: a Type structure was corrupted |
| Format: | %s - function detecting error |
| Error: | ERROR_duplicate_declaration |
| Defined In: | Scope |
| Severity: | SEVERITY_ERROR |
| Meaning: | A symbol was redeclared in the same scope |
| Format: | %s - name of redeclared symbol %d - line number of previous declaration |
| Error: | ERROR_inappropriate_use |
| Defined In: | Scope |
| Severity: | SEVERITY_ERROR |
| Meaning: | A symbol was used in a context which is inappropriate for its declaration. |
| Format: | %s - the name of the symbol |
| Error: | ERROR_include_file |
| Defined In: | Scanner |
| Severity: | SEVERITY_ERROR |
| Meaning: | An INCLUDED file could not be opened. |
| Format: | %s - the name of the file |
| Error: | ERROR_integer_expression_expected |
| Defined In: | Expression |
| Severity: | SEVERITY_WARNING |
| Meaning: | A non-integer expression was encountered in an integer-only context |
| Format: | -- none -- |
| Error: | ERROR_integer_literal_expected |
| Defined In: | Expression |
| Severity: | SEVERITY_WARNING |
| Meaning: | A non-integer or non-literal was encountered in an integer-literal context |
| Format: | -- none -- |
| Error: | ERROR_logical_literal_expected |
| Defined In: | Expression |
| Severity: | SEVERITY_WARNING |
| Meaning: | A non-logical or non-literal was encountered in a logical-literal context |
| Format: | -- none -- |
| Error: | ERROR_missing_subtype |
| Defined In: | Pass2 |
| Severity: | SEVERITY_WARNING |
| Meaning: | An entity which lists a particular supertype does not appear in that entity's subtype list. |
| Format: | %s - the name of the subtype %s - the name of the supertype |

| | |
|--------------------|---|
| Error: | ERROR_missing_supertype |
| Defined In: | Pass2 |
| Severity: | SEVERITY_ERROR |
| Meaning: | An entity which lists a particular subtype does not appear in that entity's supertype list. |
| Format: | %s - the name of the supertype %s - the name of the subtype |
| Error: | ERROR_nested_comment |
| Defined In: | Scanner |
| Severity: | SEVERITY_WARNING |
| Meaning: | A start comment symbol (* was encountered within a comment. |
| Format: | -- none -- |
| Error: | ERROR_overloaded_attribute |
| Defined In: | Pass2 |
| Severity: | SEVERITY_ERROR |
| Meaning: | An attribute name was previously declared in a supertype |
| Format: | %s - the attribute name %s - the name of the supertype with the previous declaration |
| Error: | ERROR_real_literal_expected |
| Defined In: | Expression |
| Severity: | SEVERITY_WARNING |
| Meaning: | A non-real or non-literal was encountered in a real-literal context |
| Format: | -- none -- |
| Error: | ERROR_set_literal_expected |
| Defined In: | Expression |
| Severity: | SEVERITY_WARNING |
| Meaning: | A non-set or non-literal was encountered in a set-literal context |
| Format: | -- none -- |
| Error: | ERROR_set_scan_set_expected |
| Defined In: | Loop_Control |
| Severity: | SEVERITY_WARNING |
| Meaning: | The control set for a set scan control is not a set |
| Format: | -- none -- |
| Error: | ERROR_shadowed_declaration |
| Defined In: | Pass2 |
| Severity: | SEVERITY_WARNING |
| Meaning: | A symbol declaration shadows a definition in an outer (or assumed) scope. |
| Format: | %s - name of redeclared symbol %d - line number of previous declaration |
| Error: | ERROR_string_literal_expected |
| Defined In: | Expression |
| Severity: | SEVERITY_WARNING |
| Meaning: | A non-string or non-literal was encountered in a string-literal context |
| Format: | -- none -- |

| | |
|--------------------|--|
| Error: | ERROR_syntax |
| Defined In: | Express |
| Severity: | SEVERITY_EXIT |
| Meaning: | Unrecoverable syntax error |
| Format: | %s - description of error %s - name of scope in which error occurred |
| Error | ERROR_undefined_identifier |
| Defined In: | Pass2 |
| Severity: | SEVERITY_WARNING |
| Meaning: | An identifier was referenced which has not been declared. This error only produces a warning because Fed-X does not deal with all of the scoping issues in algorithms. |
| Format: | %s - the name of the identifier |
| Error: | ERROR_undefined_type |
| Defined In: | Pass2 |
| Severity: | SEVERITY_ERROR |
| Meaning: | An undeclared identifier was used in a context which requires a type. |
| Format: | %s - the name of the type |
| Error: | ERROR_unknown_expression_class |
| Defined In: | Expression |
| Severity: | SEVERITY_DUMP |
| Meaning: | Fed-X internal error |
| Format: | %d - the offending expression class %s - the context (function) in which the error occurred |
| Error: | ERROR_unknown_schema |
| Defined In: | Pass2 |
| Severity: | SEVERITY_WARNING |
| Meaning: | An unknown schema was ASSUMEd |
| Format: | %s - the assumed schema name |
| Error: | ERROR_unknown_subtype |
| Defined In: | Pass2 |
| Severity: | SEVERITY_WARNING |
| Meaning: | An entity lists a subtype which is not itself declared as an entity. |
| Format: | %s - the subtype name %s - the supertype name |
| Error: | ERROR_unknown_supertype |
| Defined In: | Pass2 |
| Severity: | SEVERITY_EXIT |
| Meaning: | An entity lists a supertype which is not itself declared as an entity. Fed-X is unable to proceed in this situation. |
| Format: | %s - the supertype name %s - the subtype name |

Error: ERROR_unknown_type_class
Defined In: Type
Severity: SEVERITY_DUMP
Meaning: Fed-X internal error
Format: %d - the offending type class
 %s - the context (function) in which the error occurred

Error: ERROR_wrong_operand_count
Defined In: Expression
Severity: SEVERITY_WARNING
Meaning: Mismatch between actual and expected (on the basis of code context) operand count
Format: %s - the operator

A References

- [Altemeuller88] Altemeuller, J., Mapping from Express to Physical File Structure, ISO TC184/SC4/WG1 Document N280, September, 1988
- [ANSI89] American National Standards Institute, Programming Language C, Document ANSI X3.159-1989
- [Clark90a] Clark, S. N., An Introduction to The NIST PDES Toolkit, NISTIR 4336, National Institute of Standards and Technology, Gaithersburg, MD, May 1990
- [Clark90b] Clark, S.N., Fed-X: The NIST Express Translator, NISTIR 4371, National Institute of Standards and Technology, Gaithersburg, MD, August 1990
- [Clark90c] Clark, S.N., The NIST PDES Toolkit: Technical Fundamentals, NISTIR 4335, National Institute of Standards and Technology, Gaithersburg, MD, May 1990
- [Clark90d] Clark, S.N., The NIST Working Form for STEP, NISTIR 4351, National Institute of Standards and Technology, Gaithersburg, MD, June 1990
- [Clark90e] Clark, S.N., NIST STEP Working Form Programmer's Reference, NISTIR 4353, National Institute of Standards and Technology, Gaithersburg, MD, June 1990
- [Schenck90] Schenck, D., ed., Exchange of Product Model Data - Part 11: The Express Language, ISO TC184/SC4 Document N64, July 1990
- [Smith88] Smith, B., and G. Rinaudot, eds., Product Data Exchange Specification First Working Draft, NISTIR 88-4004, National Institute of Standards and Technology, Gaithersburg, MD, December 1988

ORDER and INFORMATION FORM

MAIL TO:

NATIONAL



TESTBED

National Institute of Standards and Technology
Gaithersburg MD., 20899
Metrology Building, Rm-A127
Attn: Secretary National PDES Testbed
(301) 975-3508

Please send the following documents
and/or software:

- ☐ Clark, S.N., An Introduction to The NIST PDES Toolkit
- ☐ Clark, S.N., The NIST PDES Toolkit: Technical Fundamentals
- ☐ Clark, S.N., Fed-X: The NIST Express Translator
- ☐ Clark, S.N., The NIST Working Form for STEP
- ☐ Clark, S.N., NIST Express Working Form Programmer's Reference
- ☐ Clark, S.N., NIST STEP Working Form Programmer's Reference,
- ☐ Clark, S.N., ODES User's Guide
- ☐ Clark, S.N., ODES Administrative Guide
- ☐ Morris, K.C., Translating Express to SQL: A User's Guide
- ☐ Nickerson, D., The NIST SQL Database Loader: STEP Working Form to SQL
- ☐ Strouse, K., McLay, M., The PDES Testbed User Guide

OTHER (PLEASE SPECIFY)

These documents and corresponding software will be available from NTIS in the future. When available, the NTIS ordering information will be forthcoming.

BIBLIOGRAPHIC DATA SHEET

4. TITLE AND SUBTITLE

NIST Express Working Form Programmer's Reference

5. AUTHOR(S)

Stephen Nowland Clark

6. PERFORMING ORGANIZATION (IF JOINT OR OTHER THAN NIST, SEE INSTRUCTIONS)

U.S. DEPARTMENT OF COMMERCE
NATIONAL INSTITUTE OF STANDARDS AND TECHNOLOGY
GAITHERSBURG, MD 20899

7. CONTRACT/GRANT NUMBER

8. TYPE OF REPORT AND PERIOD COVERED

9. SPONSORING ORGANIZATION NAME AND COMPLETE ADDRESS (STREET, CITY, STATE, ZIP)

10. SUPPLEMENTARY NOTES

☐ DOCUMENT DESCRIBES A COMPUTER PROGRAM; SF-185, FPS SOFTWARE SUMMARY, IS ATTACHED.

11. ABSTRACT (A 200-WORD OR LESS FACTUAL SUMMARY OF MOST SIGNIFICANT INFORMATION. IF DOCUMENT INCLUDES A SIGNIFICANT BIBLIOGRAPHY OR LITERATURE SURVEY, MENTION IT HERE.)

The Product Data Exchange Specification (PDES) is an emerging standard for the exchange of product information among various manufacturing applications. PDES includes an information model written in the Express language; other PDES-related information models are also written in Express. The National PDES Testbed at NIST has developed software to manipulate and translate Express models. This software consists of an in-memory working form and an associated Express language parser, Fed-X. The internal operation of the Fed-X parser is described. The implementation of the data abstractions which make up the Express Working Form is discussed, and specifications are given for the Working Form access functions. The creation of Express language translators using Fed-X is discussed.

12. KEY WORDS (6 TO 12 ENTRIES; ALPHABETICAL ORDER; CAPITALIZE ONLY PROPER NAMES; AND SEPARATE KEY WORDS BY SEMICOLONS)

data modeling; Express; PDES; schema translation; STEP

13. AVAILABILITY

☒

UNLIMITED

☐

FOR OFFICIAL DISTRIBUTION. DO NOT RELEASE TO NATIONAL TECHNICAL INFORMATION SERVICE (NTIS).

☐ORDER FROM SUPERINTENDENT OF DOCUMENTS, U.S. GOVERNMENT PRINTING OFFICE,
WASHINGTON, DC 20402.☒

ORDER FROM NATIONAL TECHNICAL INFORMATION SERVICE (NTIS), SPRINGFIELD, VA 22161.

14. NUMBER OF PRINTED PAGES

53

15. PRICE

A04

ELECTRONIC FORM

